

SPR スプルーリーマ

Sprue reamers



■材質：HSS-Co

呼称	両角	先径	太径	刃長	全長	柄径
	φ	φ	φ1	ℓ	L	s
20-1	2°	2.0	4.1	60	110	6
20-2	2°	2.0	5.5	100	150	6
20-5	2°	3.0	5.1	60	110	6
20-6	2°	3.0	6.5	100	150	8
20-7	2°	3.0	9.6	160	210	8
20-10	2°	4.0	6.8	80	130	8
20-11	2°	4.0	8.2	120	170	8
20-12	2°	4.0	9.6	160	210	10
20-15	2°	5.0	9.2	120	170	8
20-16	2°	5.0	10.6	160	210	10
25-1	2°30'	2.0	4.6	60	110	6
25-5	2°30'	3.0	5.6	60	110	6
25-11	2°30'	4.0	9.2	120	170	8
25-12	2°30'	4.0	11.0	160	210	10
25-15	2°30'	5.0	10.2	120	170	10
25-16	2°30'	5.0	12	160	210	12
30-1	3°	2.0	5.1	60	110	6
30-2	3°	2.0	7.2	100	150	8
30-5	3°	3.0	6.1	60	110	8
30-6	3°	3.0	8.2	100	150	8
30-7	3°	3.0	11.4	160	210	12
30-10	3°	4.0	8.2	80	130	8
30-11	3°	4.0	10.3	120	170	10
30-12	3°	4.0	12.4	160	210	12
30-15	3°	5.0	11.3	120	170	12
30-16	3°	5.0	13.4	160	210	12
35-1	3°30'	2.0	5.7	60	110	6
35-5	3°30'	3.0	6.7	60	110	8
35-11	3°30'	4.0	11.3	120	170	12
35-12	3°30'	4.0	13.8	160	210	12
35-15	3°30'	5.0	12.3	120	170	12
35-16	3°30'	5.0	14.8	160	210	12
40-1	4°	2.0	6.2	60	110	8
40-2	4°	2.0	9.0	100	150	8
40-5	4°	3.0	7.2	60	110	8
40-6	4°	3.0	10	100	150	10
40-7	4°	3.0	14.2	160	210	12
40-10	4°	4.0	9.6	80	130	10
40-11	4°	4.0	12.4	120	170	12
40-12	4°	4.0	15.2	160	210	12
40-15	4°	5.0	13.4	120	170	12
40-16	4°	5.0	16.2	160	210	12